












## STAIRLIFTS

						
	HELIX CURVED STAIRLIFT	PINNACLE STAIRLIFT	PINNACLE PREMIUM STAIRLIFT	PINNACLE HEAVY DUTY STAIRLIFT	SUMMIT AC STAIRLIFT	SUMMIT OUTDOOR STAIRLIFT
<b>MODEL NUMBERS</b>	CSL500 Series	SSL-SL300	SSL-SL600	SSL-SL600-HD	SL350AC	SL350OD
<b>WEIGHT CAPACITY</b>	350 lb	300 lb	350 lb	600 lb	- 350 lb up to 15' 9" track - 250 lb for 15' 10" 25' track	- 350 lb up to 15' 9" track - 250 lb for 15' 10" 25' track
<b>POWER SOURCE</b>	2-12V 8AH batteries	2-12V 8AH batteries	2-12V 8AH batteries	2-12V 8AH batteries	115V household AC	115V household AC
<b>DRIVE SYSTEM</b>	Steel rack and pinion	- Patented nylon polymer gear rack - Helical worm gear	- Patented nylon polymer gear rack - Helical worm gear	- Patented nylon polymer gear rack - Helical worm gear	AC Powered: cable drive system	AC Powered: Cable drive system
<b>SEAT BOTTOM SIZE</b>	19" x 15"	19" x 16"	19" x 16"	18.5" x 14"	17.5" x 14"	17.5" x 14"
<b>SEAT BACKREST SIZE</b>	14" x 16"	16.5" x 9.5" Adjustable 1" up or down	17.5" x 17"	17.6" x 17"	18.5" x 9"	18.5" x 9"
<b>FOOTREST SIZE</b>	11" x 12"	12.6" x 14.8"	12.3" x 13.2" 17" - 22" height adjustable	12.3" x 13.2"	9.5" x 10"	9.5" x 10"
<b>SPEED</b>	20 FPM	20 FPM	20 FPM	14 FPM	20 FPM	20 FPM
<b>FOLDED WIDTH</b>	16" from wall	- 11" from wall - 13.6" with folding rail	- 10 1/2" from wall - 13.6" with folding rail	16.5" from wall	14" from wall	14" from wall
<b>INCLINE LIMITS</b>	up to 58°	27° to 52°* *inclines above 45° may require local jurisdiction approval.	27° to 52°* *inclines above 45° may require local jurisdiction approval.	27° to 48°* *inclines above 45° may require local jurisdiction approval.	35° to 45°	35° to 45°
<b>CERTIFIED</b>	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial & residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial and residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial and residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial or residential	- Not ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated residential
<b>WARRANTY</b>	- Limited lifetime on drive system, structure - 2-year parts - 1-year battery	- 2-year parts - 10-year gear rack - 1-year battery	- Limited lifetime on drive system, structure - 1-year battery	- 3-year parts - 10-year gear rack - 1-year battery	2-year parts	2-year parts
<b>OPTIONS</b>	- Emergency stop button - Key switch - Additional call/send - Additional charging station - Black or beige rail, chassis, upholstery - Outdoor package	- Automatic folding rail - Chassis obstruction sensor - Extra rail + brackets - Key lock - Manual lowering tool - Power Footrest - Power Swivel - Retractable seatbelt	- Automatic folding rail - Extra rail - Key lock - Manual lowering tool - Power Footrest - Power Swivel	- Key lock - Extra rail - Manual lowering tool	- Key lock - Extra rail - Flip up armrests - Grocery basket	- Key lock - Extra rail

## PLATFORM LIFTS

			
	HIGHLANDER II SERIES VPL	HIGHLANDER II WITH ENCLOSURE	HIGHLANDER II 400-X VPL
<b>MODEL NUMBERS</b>	VPL400 - VPL1400	VPL400 - VPL1400	VPL400-X
<b>WEIGHT CAPACITY</b>	750 lb	750 lb	750 lb
<b>LIFTING HEIGHT</b>	- VPL400: up to 53" - VPL600: up to 77" - VPL800: up to 101" - VPL1000: up to 125" - VPL1200: up to 149" - VPL1400: up to 171"	- VPL400: up to 53" - VPL600: up to 77" - VPL800: up to 101" - VPL1000: up to 125" - VPL1200: up to 149" - VPL1400: up to 171"	VPL400-X: up to 53"
<b>DRIVE</b>	- ACME screw - 90V 3/8 HP fully sealed DC gear motor	- ACME screw - 90V 3/8 HP fully sealed DC gear motor	- ACME screw - 90V 3/8 HP fully sealed DC gear motor
<b>POWER</b>	- 120V AC - 15 AMP circuit breaker	- 120V AC - 15 AMP circuit breaker	- 120V AC - 15 AMP circuit breaker
<b>PLATFORM SIZES</b>	- 36" x 48" clear platform with 36" guard panel - 36" x 54" clear platform with 42" guard panel - 36" x 60" clear platform with 42" guard panel - 42" x 54" clear platform with 42" guard panel - 42" x 60" clear platform with 42" guard panel	- 36" x 60" clear platform with 42" guard panel - 42" x 60" clear platform with 42" guard panel	- 36" x 48" clear platform with 36" guard panel - 36" x 54" clear platform with 42" guard panel - 36" x 60" clear platform with 42" guard panel - 42" x 54" clear platform with 42" guard panel - 42" x 60" clear platform with 42" guard panel
<b>SPEED</b>	9.5 to 15 FPM	9.5 to 15 FPM	9.5 to 15 FPM
<b>FOOTPRINT</b>	- VPL400-VPL600: 52" x 70" - VPL800-VPL1400: 52" x 56"	- 36 clear: 59" x 68.5" /92" with fixed ramp - 42 clear: 65" x 68.5" /92" with fixed ramp	53" x 48" - 59" x 62"
<b>CERTIFIED</b>	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial and residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial and residential	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated residential
<b>WARRANTY</b>	- 3-year parts - 1-year battery (if included)	- 3-year parts - 1-year battery (if included)	2-year parts
<b>OPTIONS</b>	- Battery backup UPS system - 36" or 42" platform gates with EMI interlock - Grab bar in platform - Key lock in platform - 36" or 42" landing gates with interlock - Fire-rated doors - Enclosure kits - Phone jack - Fixed or auto-fold ramp - Wired or wireless call/send controls - Lighted E-Stop with alarm - 3-stop with 3-button control panel	- 3-stop with 3-button control panel - 36" or 42" upper landing door with EMI interlock - Battery backup UPS system - Fire-rated doors - Grab bar in platform - Key lock in platform - Safety pan - Wired or wireless call/send control	- 36" or 42" platform gates with EMI interlock - Key lock in platform - 36" or 42" landing gates with interlock - Fixed or auto-fold ramp